

SB Series

STRAW BLOWERS



**AUTOMATIC
BALE
FEED**



Automatic bale feed
processes entire bale.
No more slab feeding.

1^{1/2} TO 2
BALES PER MINUTE



1-1/2 to 2 bales per
minute output.

**AVAILABLE
DRIVES**



Engine driven, PTO
or Skid Steer drive
available.

50^{FT}
DISCHARGE



50 ft discharge.

STRAW BLOWER SPECIFICATIONS

Model	SB 1800	SB 1300	SB 5400	SB3000
Power Source	Honda™ 18 hp	Honda™ 13 hp	PTO 540	Skid Steer Hydraulic System
Power Discharge	50-55 ft.	45-50 ft.	60-70 ft. distance with 6" x 30' hosewith	60-70 ft. distance 6" x 30' hose
Dimensions	31"W x 51"L x 55"H	31"W x 51"L x 55"H	31"W x 55"L x 60"H	31"W x 55"L x 60"H
Weight	500 lb.	460 lb.	525 lb.	540 lb.
Bales/Minute	1.5-2	1-1.5	1-2	1-2
Rotor	16" dia./32 knives	16" dia./32 knives	16" dia./32 knives	16" dia./32 knives
Steel Impeller	18" dia./25" steel	18" dia./25" steel	18" dia./25" steel	18" dia./25" steel

The manufacturer reserves the right to make changes in engineering, design and specifications or add improvements at any time without notice or obligation.

HARPER®
Goossen